

Applications Design and Development, a case study of the EDA Summarize-Each-Variable Suite

Ronald J. Fehd Senior Maverick
Theoretical Programmer Stakana Analytics

Abstract **Description :** This presentation shows the programming steps in the development of an Exploratory Data Analysis (EDA) application.

Purpose : The case study consists of six files which summarize each variable in any specified data set. The discipline shows how to write programs and conduct both unit and integration tests. The emphasis is on writing small, easy to read programs, which may be converted to macros at a later time. Global macro variables are used as parameters. This unit is the first of four of a planned day-long seminar on applications development for programmers.

Audience : beginning programmers and intermediate to advanced users

In this paper	Research, Contents Procedure	3
	Bottom Up, Frequency Procedure	4
	Data Structure	7
	Top Down, Making List of Variable Names	10
	Processing the List	11
	Change Notice, Adjustments for Summary Procedure	14
	Process the Subset	16
	Next-to-Last Review	16
	Summary	17
	Program Listings, Summarize-Each-Variable Suite	18
	Suite.1 Frequency of All Variables	18
	Suite.2 Frequency or Summary	19
	Program Listings, testing programs	21
	Bibliography	22

Quote Information is *the* difference that makes *a* difference Gregory Bateson, 1904–1980
Steps to an Ecology of Mind, 1972

- Checklist of Ideas**
- cardinality ratio n-levels, n-obs
 - categories of variables few many row-id
discrete continuous unique
 - guarantee quality, readable, tested
 - list contains items, tasks, or lists Polish notation
 - mnemonics DJD, HIPO, LATCH
 - requirements, design, 80/20, specifications change notice
 - style guide naming conventions
 - data structure less than 1% of statements
99% of success
 - global macro variables parameters
 - hierarchy of program types module, routine, or subroutine
 - know thy options prepare for testing
 - small is beautiful easy to test
 - use SAS naming conventions avoid quirks!

time budget This table shows the time spent during applications development.

Phase	Time	Action	Time
design	1/2	understand problem:	1/3
		education and research	
testing	1/2	development coding	1/6
		component or unit test	1/4
		systems or integration test	1/4

The Mythical Man-Month, by Fred Brooks, on the development of the IBM 360

EDA requirements for each variable in a data set, perform frequency

<u>module</u>	<u>routine</u>	<u>subroutine</u>
01-data-class		
proc-1-freq		make-list-vars
	proc-list-vars	proc-freq

Compare to Change Notice requirements on page 14.

discipline of applications development

- hard-coded absolute
- soft-coded relative
- split into use macro variables as parameters
- testing subroutine.sas
subroutine-test.sas
- testing unit integration

Research, Contents Procedure

contents sashelp.class

```

1 PROC contents data = sashelp.class

Data Set Name SASHELP.CLASS Observations 19
Member Type DATA Variables 5

Created Tuesday, May 24, 2011 01:52:28 PM [granularity]
Label Student Data

Folder ...\core\sashelp\ [libref]
Filename class.sas7bdat [data set name]

Location Alphabet Time Category Hierarchy
5 Ways of Organizing Information

Alphabetic List of Variables and Attributes

Var
Num Variable Type Len
3 Age Num 8
4 Height Num 8
1 Name Char 8
2 Sex Char 1
5 Weight Num 8

Location Alphabet Time Category Hierarchy
    
```

desired program

The objective of list processing is to have SAS write statements like this program.

```

%let in_data = sashelp.class;

proc freq data = &in_data ...
    tables Age ...
    tables Height ...
    tables Name ...
    tables Sex ...
    tables Weight ...

proc display data = out_frequencies;
    
```

desired output

The output data sets are concatenated and look like this.

	valu	valu		
name	char	num	COUNT	PERCENT
-----	-----	----	-----	-----
Name	Alfred	.	1	5.263
	Alice	.	1	5.263
...				
Sex	F	.	9	47.368
	M	.	10	52.631
Age		11.0	2	10.526
		12.0	5	26.315
...				
Height		51.3	1	5.263
		56.3	1	5.263

slide 11

Bottom Up, Frequency Procedure

step.1 hard-coded

This program is the first step in applications development, getting an example program in SAS. Concatenation requires that the output data sets have a consistent data structure, i.e., same variable names. This program shows the names of variables in an output data set from the frequency procedure.

```

1  proc freq data = sashelp.class;
2      tables sex / out = out_freq_sex;
3      tables age / out = out_freq_age;
4  proc sql; describe table    out_freq_sex;
5      describe table    out_freq_age;
6      quit;

```

r11-freq.log

```

create table out_freq_sex
  Sex      char(1),
  count   num label = Frequency Count,
  percent num label = Percent of Total Frequency

create table out_freq_age
  Age      num,

```

slide 12

Notes: 1. Discipline step.1: hard-coded statements. 2. `describe table` writes to the log. 3. file-naming conventions: r1?-freq for frequency procedure.

step.2 soft-coded

This program shows the allocation of two macro variables, `in_data` and `var`, as the parameters for a sub-program.

```
1 %let in_data = sashelp.class;
2 %let var     = sex;
3
4 proc freq data = &in_data;
5     tables &var / out = out_freq;
6
7 proc sql; describe table &syslast;
8     quit;
```

slide 13

Notes: 1. Discipline step.2: soft-coded statements, using global macro variables as parameters. 2. `syslast` is a global automatic macro variable, which contains the two-level name of the data set created in the previous step.

step.3.1 split into called

This sub-program shows the references of the two macro variables, `in_data` and `var`, as the parameters for this called sub-routine.

```
1 proc freq data = &in_data;
2     tables &var / noprint
3     out = out_freq
4     (rename = (&var = valu_&type ));
5
6 proc sql; describe table &syslast;
7     quit;
8
9 proc append data = &syslast
10    base = out_data;
```

slide 14

Notes: 1. Discipline step.3: split soft-coded program into two programs. 2. Lines 5-6, see program `describe`, page 11. 3. Style guide: use white space to group keywords and arguments in vertical columns.

step.3.2 ... and caller

This program shows the allocation of two macro variables, `in_data` and `var`, and the call of the sub-routine.

```

1  %let in_data = sashelp.class;
2
3  %let var = sex;
4  %let type = c;
5  %include 'r13-freq.sas'/source2;
6
7  %let var = age;
8  %let type = n;
9  %include 'r13-freq.sas'/source2;
10
11 proc print data = &syslast;
12 run;

```

slide 15

Notes: 1. lines 5, 9; option `source2` is a global option, shown in next program, and option of the `%include` statement; it echoes the statements in the file to the log. 2. The object is described first and then the verb. This is an example of a task written in Reverse Polish Notation, i.e., the verb after the object comes. Why Yoda famous was. 3. Polish notation: $2+2=4$:: infix notation; $+ 2 2$:: prefix notation; $2 2 +$ reverse notation.

debugging

```

NOTE: Appending WORK.OUT_FREQ to WORK.OUT_DATA.
WARNING: Variable valu_N was not found on BASE file.
      ^
WARNING: Variable valu_C was not found on DATA file.
      ^
ERROR: No appending done because of anomalies listed above.
NOTE: Statements not processed because of errors noted above.

```

slide 16

Data Structure

polishing data structure

Data sets to be appended must have same variable names. The variable is renamed in the frequency procedure output data set and the data step then adds the other variable name.

```

1 PROC freq data = &in_data;
2     tables &var / noprint
3     out = out_freq
4     (rename =(&var = valu_&type) );
5
6 DATA freq_values;
7     attrib valu_c length = $32
8     valu_n length = 8;
9     set &syslast;
10
11 PROC append data = &syslast
12     base = out_data;
13 run;
```

slide 17

Notes: 1. Data structure may be as small as <1% of program statements. 2. Style guide, the naming convention for variables `valu-c` and `valu-n` depends on the parameter `type`.

polishing test program

This program shows the principle of allocating a macro variable – `proc_name` — to replace any set of two or more occurrences of the same string.

```

1 options source2;
2 %let in_data = sashelp.class;
3 %let proc_name = 'r14-freq.sas';
4
5 %let var = sex;
6 %let type = c;
7 %include &proc_name;
8
9 %let var = age;
10 %let type = n;
11 %include &proc_name;
12
13 proc print data = &syslast;
14 run;
```

slide 18

Notes: 1. Option `source2` is a global option; it has been moved from the `%include` statement. 2. Macro variable `proc_name` reduces typing and the need for find-and-replace. Compare to previous program, `r13-freq-test`.

output, first draft

Obs	valu_c	valu_n	COUNT	PERCENT
1	F	.	9	47.3684
2	M	.	10	52.6316
3		11	2	10.5263
4		12	5	26.3158
...				
7		15	4	21.0526
8		16	1	5.2632

slide 19

Notes: Each row is from which variable?

polishing data structure

Add a variable name 'var' and retain the name of the variable.

```

1 PROC freq data = &in_data;
2     tables &var / noprint
3     out = out_freq
4     (rename =(&var = valu_&type) );

6 DATA freq_values;
7     attrib var length = $32
8     valu_c length = $32
9     valu_n length = 8;
10    retain var "&var";
11 set &syslast;
12
13 PROC append data = &syslast
14     base = &out_data;
15 run;
```

slide 20

Notes: 1. The name of the variable, `var`, is placed first in the data structure. 2. Style guide: always end routine or subroutine with a `run;` statement.

polishing test program

```

1  options source2;
2  %let in_data  = sashelp.class;
3  %let out_data = work.out_data;
4  %let proc_name = 'r15-freq.sas';
5
6  %let var = sex;
7  %let type = c;
8  %include &proc_name;
9
10 %let var = age;
11 %let type = n;
12 %include &proc_name;
13
14 proc print data = &out_data;
15 run;

```

slide 21

output, 2nd rough draft

Obs	var	valu_c	valu_n	COUNT	PERCENT
1	sex	F	.	9	47.3684
2	sex	M	.	10	52.6316
3	age		11	2	10.5263
4	age		12	5	26.3158
5	age		13	3	15.7895
6	age		14	4	21.0526
7	age		15	4	21.0526
8	age		16	1	5.2632

slide 22

output, polished

```

1  PROC print data = &out_data;
2      title3 &out_data;
3      title4 &in_data ;
4      by name notsorted;
5      id name;
6  run;

```

slide 23

Notes: Consider using ODS for other destinations.

var	valu_c	valu_n	COUNT	PERCENT
sex	F	.	9	47.3684
	M	.	10	52.6316
age		11	2	10.5263
		12	5	26.3158
		13	3	15.7895
		14	4	21.0526
		15	4	21.0526
		16	1	5.2632

slide 24

Notes: Information: double-digit percents indicate variable is discrete.

Top Down, Making List of Variable Names

echo data structure

This sql program lists the data structure in the log.

```
1 PROC sql; describe table sashelp.class;
2           describe table dictionary.columns;
3           quit;
```

r21-sql-describe.log

```
create table SASHELP.CLASS( label='Student Data')
  Name   char(8),
  Sex    char(1),
  Age    num,
  Height num,
  Weight num
```

slide 25

Notes: We want a data set with this information.

sql dictionary columns

This is the data structure of the sql dictionary columns.

```
NOTE: SQL table Dictionary.Columns was created like:
  libname char(8)   label='Library Name',
  memname char(32) label='Member Name',
  memtype char(8)  label='Member Type',
  name     char(32) label='Column Name',
  type     char(4)  label='Column Type',
  length  num      label='Column Length',
  varnum  num      label='Column Number in Table',
```

slide 26

Notes: Compare to describe view sashelp.vcolumns;

making list of variable names

This sql program makes a list of the variable names in a data set.

```
1 PROC sql; create table list_variables as
2           select libname, memname, name, type
3           from   dictionary.columns
4           where  libname eq "%upcase(&libname)"
5                 and memname eq "%upcase(&memname)";
6           quit;
```

slide 27

Notes: 1. Save this program as `make-list-vars-sql.sas`.
2. Notice the use of SAS naming conventions to promote readability and reuse.

subroutine for testing

This sql program echos the data structure to the log and prints the data set.

```

1 PROC sql; describe table &syslast;
2           quit;
3 PROC print data = &syslast;
4           title3 &syslast;
5 run;

```

slide 28

Notes: 1. Programmers want to read the notes in the log produced by sql; users want to examine the output from the print procedure. 2. This is from `r12-freq` on page 5.

**testing subroutine
make-list**

```

1 %let libname = sashelp;
2 %let memname = class;
3 %include 'r22-sql-make-list.sas';
4 %include 'describe.sas';

```

slide 29

a control data set

Obs	libname	memname	name	type
1	SASHELP	CLASS	Name	char
2	SASHELP	CLASS	Sex	char
3	SASHELP	CLASS	Age	num
4	SASHELP	CLASS	Height	num
5	SASHELP	CLASS	Weight	num

slide 30

Processing the List**demo.1 of sql text**

Notes: The first few lines of program `r31-sql-proc-text-demo.sas` are not shown on the slide.

```

1 %let libname = sashelp;
2 %let memname = class;
3 %include 'make-list-vars-sql.sas';

5 PROC sql; select 'prefix', name, 'etc', type, 'suffix'
6           from list_variables;
7           quit;

```

r31-sql-proc-text-demo.lst

	Name		Type	
prefix	Name	etc	char	suffix
prefix	Sex	etc	char	suffix
prefix	Age	etc	num	suffix
prefix	Height	etc	num	suffix
prefix	Weight	etc	num	suffix

slide 31

demo.2 of sql text

```

5 PROC sql; select '%let name=', name, ';'
6               , '%let type=', type, ';'
7               from list_variables;
8               quit;

```

r32-sql-proc-text-let.lst

Name	Type
%let name= Name	;%let type= char ;
%let name= Sex	;%let type= char ;
%let name= Age	;%let type= num ;
%let name= Height	;%let type= num ;
%let name= Weight	;%let type= num ;

slide 32

Notes: 1. Test program, r33-sql-proc-list-test, is not shown in the slides.
 2. Program r22-sql-make-list on page 11 is the predecessor of make-list-vars-sql.

calling routine

```

1 %let libname = sashelp;
2 %let memname = class;
3 %include 'make-list-vars-sql.sas';
4
5 %let proc_name = 'put-name-type.sas';
6 %include 'r33-sql-proc-list.sas';

```

Notes: This test program, put-name-type.sas, is not shown in the slides.

```

1 %put note: &=name &=type;

```

called subroutine

```

1 PROC sql; select catt('%let name=', name, ';'
2                   , '%let type=', type, ';'
3                   , "%include &proc_name ;")
4               into :proc_list separated by ' '
5               from list_variables;
6               quit;
7 &proc_list

```

r33-sql-proc-list.lst

```

%let name=Name ;%let type=char;%include 'put-name-type.sas';
%let name=Sex ;%let type=char;%include 'put-name-type.sas';
%let name=Age ;%let type=num ;%include 'put-name-type.sas';
%let name=Height;%let type=num ;%include 'put-name-type.sas';
%let name=Weight;%let type=num ;%include 'put-name-type.sas';

```

slide 33

Notes: Save r33-sql-proc-list-test.sas as proc-list-vars.sas, as shown on page 18.

using SAS names

This program has four parameters, libname, memname, name and type.

```

1 PROC freq data = &libname.&memname;
2     tables &name / noprint
3     out = out_freq
4     (rename =(&name = valu_&type) );
5
6 DATA freq_values;
7     attrib name length = $32
8     valu_char length = $32
9     valu_num length = 8;
10    retain name "&name";

```

slide 34

Notes: Naming conventions: programs for the frequency procedure have the prefix `r1`.

first review

```

1 %let in_data = sashelp.class;
2 %let libname = %scan(&in_data, 1, .);
3 %let memname = %scan(&in_data, -1, .);
4 %let out_data = work.out_data;
5
6 %include 'make-list-vars-sql.sas';
7
8 %let proc_name = 'r16-freq.sas';
9 %include 'r33-sql-proc-list.sas';
10
11 %include 'proc-print-out-data.sas';

```

slide 35

Notes: Compare to `proc-1-freq.sas`, shown on page 18.

name	valu_	valu_num	COUNT	PERCENT
	char			
Name	Alfred	.	1	5.2632
	Alice	.	1	5.2632
...				
	Thomas	.	1	5.2632
	William	.	1	5.2632
Sex	F	.	9	47.3684
	M	.	10	52.6316

slide 36

Notes: For variable *Name* count equals 1 for all values; this means it is unique, the row-identifier.

Age	11.0	2	10.5263
	12.0	5	26.3158
...			
	15.0	4	21.0526
	16.0	1	5.2632
Height	51.3	1	5.2632
...			
	62.5	2	10.5263
...			
	66.5	2	10.5263
	72.0	1	5.2632

slide 37

Notes: 1. For classification variable Age, n-levels = 6, this means it is discrete.
 2. For fact variable Height, many instances of count=1, this means it is continuous.

Change Notice, Adjustments for Summary Procedure

requirements, v2

from: for each variable in a data set, perform frequency
 to: for any data set

1. character variables, frequency
2. numeric variables, summary

<u>module</u>	<u>routine</u>	<u>subroutine</u>
02-data*		
proc-2-freq-smry		make-list-vars-sql
	proc-list-vars-subset	
	proc-freq	data-structure
	proc-summary	

Notes: Compare to first requirements on page 2.

proc summary

r51-smry.sas is not shown in the slides.

```

1 PROC summary data = sashelp.class;
2     var height;
3     output
4         out = out_summary;
5 %include 'describe.sas';

```

Notes: Style guide: align keywords, equal sign, and arguments. Readability promotes reuse.

step.2 soft-coded

```

1 %let libname = sashelp;
2 %let memname = class;
3 %let name = height;
4
5 PROC summary data = &libname.&memname;
6     var &name;
7     output
8         out = out_summary;
9 %include 'describe.sas';

```

slide 39

data structure

```

create table work.out_summary
    (label='Summary Statistics')
    _TYPE_ num,
    _FREQ_ num,
    _STAT_ char(8),
    Height num

```

r52-smry-test.lst

Obs	_TYPE_	_FREQ_	_STAT_	Height
1	0	19	N	19.0000
2	0	19	MIN	51.3000
3	0	19	MAX	72.0000
4	0	19	MEAN	62.3368
5	0	19	STD	5.1271

slide 40

Notes: r53-smry.sas is not shown in the slides.

```

1 PROC summary data = &libname..&memname;
2     var          &name;
3     output
4         out = out_summary
5         ( drop = _type_ _freq_
6           rename = (_stat_ = valu_char
7                     &name = valu_num));
8 %include 'describe.sas';

```

Note: Style, naming conventions: the suffix of the variables named valu-* is in ('char','num'), which is the value of the variable type in the control data set.

proc summary

```

1 PROC summary data = &libname..&memname;
2     var          &name;
3     output
4         out = out_summary
5         ( drop = _type_ _freq_
6           rename = (_stat_ = valu_char
7                     &name = valu_num));
8 %include 'data-structure.sas';

```

slide 41

Notes: Save r54-smry.sas as proc-summary.sas; see listing on page 20.

common subroutine

```

1 DATA standardized_data_structure
2     (label = "freq/smry of &libname &memname");
3     attrib name          length = $32
4            valu_char     length = $32 %* fragile! ;
5            valu_num      length = 8
6            count         length = 8
7            percent       length = 8;
8     retain name "&name";
9     set &syslast;
10
11 PROC append data = &syslast
12     base = &out_data;
13 run;

```

slide 42

Notes: See r16-freq.sas on page 13. See listing on page 20.

proc freq, updated

```

1 PROC freq data = &libname..&memname;
2     tables &name / noprint
3     out = out_freq
4     (rename = (&name = valu_&type));
5
6 %include 'data-structure.sas';

```

slide 43

Notes: Save r17-freq.sas as proc-freq.sas, see listing on page 20.

Process the Subset**processing a subset**

```

1 PROC sql noprint;
2     select catt('%let name=', name, ';'
3               ,'%let type=', type, ';'
4               ,"%include &proc_name ;")
5     into :proc_list separated by ' '
6     from list_variables
7     where &proc_where;      * <---<<< ;
8     quit;
9 &proc_list

```

slide 44

Notes: Save r34-sql-proc-list-where.sas as proc-list-vars-subset.sas,
see listing on page 21.

main module

```

8 %let     proc_name = 'proc-freq.sas';
9 %let     proc_where = type eq 'char';
10 %include 'proc-list-vars-subset.sas';
11
12 %let     proc_name = 'proc-summary.sas';
13 %let     proc_where = type eq 'num';
14 %include 'proc-list-vars-subset.sas';
15
16 %include 'proc-print-out-data.sas';

```

slide 45

Notes: Save r42-proc-all-both.sas as proc-2-freq-smry.sas,
see listing on page 19.

Next-to-Last Review**proc either**

name	valu_	valu_num	count	percent
Name	Alfred	.	1	5.2632
...	William	.	1	5.2632
Sex	F	.	9	47.3684
	M	.	10	52.6316
Age	N	19.000	.	.
	MIN	11.000	.	.
	MAX	16.000	.	.
	MEAN	13.316	.	.
	STD	1.493	.	.
Height	N	19.000	.	.
	MIN	51.300	.	.
	MAX	72.000	.	.
	MEAN	62.337	.	.
	STD	5.127	.	.
...				

slide 46

Program Listings, Summarize-Each-Variable Suite

Suite.1 Frequency of All Variables

<u>module</u>	<u>routine</u>	<u>subroutine</u>	<u>lines</u>
01-data*			5
proc-1-freq			16
		make-list-vars-sql	6
	proc-list-vars		10
	proc-print-out-data		7
	proc-freq		9

```

_____ 01-data-sashelp-class.sas _____
1 %let in_data = sashelp.class;
2 %let out_data = work.summary_each_var_class;
3
4 %include 'proc-1-freq.sas';

_____ proc-1-freq.sas _____
1 ***** echo included statements to log?;
2 options source2;
3
4 **** split two-level name: in_data :: libref.data;
5 %let libname = %scan(&in_data, 1,.);
6 %let memname = %scan(&in_data,-1,.);
7 %put note: &=in_data &=libname &=memname;
8
9 ***** create input list: control data set;
10 %include 'make-list-vars-sql.sas';
11
12 ***** call item processing routine;
13 %let proc_name = 'r16-freq.sas';
14 %include 'proc-list-vars.sas';
15
16 %include 'proc-print-out-data.sas';

_____ make-list-vars-sql.sas _____
1 PROC sql; create table list_variables as
2     select libname, memname, name, type
3     from dictionary.columns
4     where libname eq "%upcase(&libname)"
5     and memname eq "%upcase(&memname)";
6     quit;

_____ proc-list-vars.sas _____
1 %put note: &=proc_name;
2 *fragile: max length sql cat* values=$char200.;
3 *fragile: max length mvar = 2**16 = 64K;
4
5 PROC sql noprint;
6     select catt('%let name=', name, ';'
7             , '%let type=', type, ';'
8             , "%include &proc_name ;" )
9     into :process_list separated by ' '
10    from list_variables;
11    quit;
12 &process_list

```

Note: `proc-freq` for `suite.1` is `r16-freq`, on page 13.

```

_____ proc-print-out-data.sas _____
1 PROC print data = &out_data;
2     title3 &out_data;
3     title4 &in_data ;
4     by    name notsorted;
5     id    name;
6 run;

```

Suite.2 Frequency or Summary

<u>module</u>	<u>routine</u>	<u>subroutine</u>	<u>lines</u>
01-data*			5
proc-2-freq-smry			22
		make-list-vars-sql	6
	proc-list-vars-subset		11
	proc-print-out-data		7
		data-structure	13
	proc-freq		9
	proc-summary		11

```

_____ 02-data-sashelp-heart.sas _____
1 %let in_data = sashelp.heart;
2 %let out_data = work.summary_each_var_heart;
3
4 %include 'proc-2-freq-smry.sas';

```

```

_____ proc-2-freq-smry.sas _____
1 ***** echo included statements to log?;
2 *options source2;
3
4 **** split two-level in-data :: libref.data;
5 %let libname = %scan(&in_data, 1,.);
6 %let memname = %scan(&in_data,-1,.);
7 %put note: &=in_data &=libname &=memname;
8
9 ***** create input list: control data set;
10 %include 'make-list-vars-sql.sas';
11
12 ***** call item processing routines;
13 %let proc_name = 'proc-freq.sas';
14 %let proc_where = 1; * all? or only char?;
15 %let proc_where = type eq 'char';
16 %include 'proc-list-vars-subset.sas';
17
18 %let proc_name = 'proc-summary.sas';
19 %let proc_where = type eq 'num';
20 %include 'proc-list-vars-subset.sas';
21
22 %include 'proc-print-out-data.sas';

```

```

_____ proc-list-vars-subset.sas _____
1 %put note: &=proc_name &=proc_where;
2 PROC sql noprint;
3     select catt('%let name=', name, ';'

```

```

4             ,'%let type=', type, ';'
5             ,"%include &proc_name ;")
6         into :_process_list separated by ' '
7         from list_variables
8         where &proc_where;          * <---<<< ;
9         quit;
10 &_process_list

```

```

1 DATA standardized_data_structure
2     (label = "freq/smry of &libname &memname");
3     attrib name          length = $32
4           valu_char length = $32 %* fragile! ;
5           valu_num  length = 8
6           count     length = 8
7           percent   length = 8;
8     retain name "&name";
9     set &syslast;
10
11 PROC append data = &syslast
12         base = &out_data;
13 run;

```

```

1 %put note: &=libname &=memname &=name &=type;
2
3 PROC freq data  = &libname .&memname;
4     tables  &name  / noprint
5     out     = out_freq
6     (rename =(&name = valu_&type));
7
8 %include 'data-structure.sas';

```

```

1 %put note: &=libname &=memname &=name &=type;
2
3 PROC summary data  = &libname..&memname;
4     var           &name;
5     output
6     out = out_summary
7     ( drop = _type_ _freq_
8     rename = (_stat_ = valu_char
9     &name = valu_num));
10
11 %include 'data-structure.sas';

```

Program Listings, testing programs

<u>routine</u>	<u>subroutine</u>	<u>lines</u>
	make-list-vars-sql-test	6
proc-list-vars-subset-test		14
proc-freq-test		9
proc-summary-test		6
	describe	7


```

_____ make-list-vars-sql-test.sas _____
1 %let libname = sashelp;
2 %let memname = class;
3 %include 'make-list-vars-sql.sas';
4 %include 'describe.sas';

_____ proc-freq-test.sas _____
1 %let libname = sashelp;
2 %let memname = class;
3 %let out_data = out_data_&memname;
4
5 %let name = sex;
6 %let type = char;
7 %include 'proc-freq.sas';
8 %include 'describe.sas';
9
10 %let name = age;
11 %let type = num;
12 %include 'proc-freq.sas';
13 %include 'describe.sas';

_____ proc-list-vars-subset-test.sas _____
1 %let libname = sashelp;
2 %let memname = class;
3 %let out_data = work.summary_each_var_class;
4
5 %include 'make-list-vars-sql.sas';
6 %let proc_name = 'put-name-type.sas';
7 %let proc_where = 1;
8 %include 'proc-list-vars-subset.sas';

_____ proc-summary-test.sas _____
1 %let libname = sashelp;
2 %let memname = class;
3 %let out_data = out_data_&memname;
4
5 %let name = height;
6 %let type = num;
7 %include 'proc-summary.sas';
8 %include 'describe.sas';
9
10 %let name = weight;
11 %include 'proc-summary.sas';
12 %include 'describe.sas';

```

Bibliography

- [1] John E. Bentley. Software testing fundamental — concepts, roles, and terminology. In *Proceedings of the 30th Annual SAS® Users Group International Conference*, 2005. URL <http://www2.sas.com/proceedings/sugi30/141-30.pdf>. 12 pp.; theory of testing.
- [2] Frederick P. Brooks Jr. *The Mythical Man-Month: Essays on Software Engineering, Anniversary Edition, 2/E*. Addison-Wesley, 1995. URL https://en.wikipedia.org/wiki/The_Mythical_Man-Month. 322 pp., 19 chap., index: 14 pp.; theory and story based on development of IBM System/360 operating system.
- [3] Frederick P. Brooks Jr. *The Design of Design*. Addison-Wesley, 2010. URL <http://www.pearsonhighered.com/educator/product/Design-of-Design-The-Essays-from-a-Computer-Scientist/9780201362985.page>. 421 pp., 28 chap., index: 20 pp.; history of the design process in many disciplines, besides software.
- [4] Ronald J. Fehd. Writing testing-aware programs that self-report when testing options are true. In *NorthEast SAS Users Group Annual Conference Proceedings*, 2007. URL <http://www.nesug.org/Proceedings/nesug07/cc/cc12.pdf>. Coders' Corner, 20 pp.; topics: options used while testing: echoauto, mprint, source2, verbose; variable testing in data step or macros; call execute; references.
- [5] Ronald J. Fehd. FreqLibname: a data review routine for all memnames in a libname. In *NorthEast SAS Users Group Annual Conference Proceedings*, 2007. URL <http://www.nesug.org/proceedings/nesug07/cc/cc11.pdf>. Coders' Corner, 22 pp.; topics: comments, documentation, quality, theory, replacing macros with call execute of parameterized include files, saving procs freq and summary output data set; info: complete test suite of modules, routines, and subroutines, getting mode from proc freq.
- [6] Ronald J. Fehd. Journeymen's tools: Data review macro FreqAll — using Proc SQL list processing with Dictionary.Columns to eliminate macro do loops. In *SAS Global Forum Annual Conference Proceedings*, 2007. URL <http://www2.sas.com/proceedings/forum2007/028-2007.pdf>. Coder's Corner, 10 pp.; attributes, dictionary.columns, metadata, proc append, proc freq, proc sql, program header; bibliography.
- [7] Ronald J. Fehd. SmryEachVar: A data-review routine for all data sets in a libref. In *SAS Global Forum Annual Conference Proceedings*, 2008. URL <http://www2.sas.com/proceedings/forum2008/003-2008.pdf>. Applications Development, 24 pp.; call execute, data review, data structure, dynamic programming, list processing, parameterized includes, utilities (writattr, writvalu) to repair missing elements in data structure; best contributed paper in ApDev.
- [8] Ronald J. Fehd. How to use proc SQL select into for list processing. In *South Central SAS Users Group Annual Conference Proceedings*, 2010. URL <http://analytics.ncsu.edu/sesug/2010/HOW06.Fehd.pdf>. Hands On Workshop, 40 pp.; topics: writing constant text, and macro calls, using macro %do loops; references.
- [9] Ronald J. Fehd. Macro design ideas: Theory, template, practice. In *MidWest SAS Users Group Annual Conference Proceedings*, 2013. URL <http://www.mwsug.org/proceedings/2013/00/MWSUG-2013-0002.pdf>. 21 pp.; topics: logic, quality assurance, testing, style guide, documentation, bibliography.
- [10] Ronald J. Fehd and Art Carpenter. List processing basics: Creating and using lists of macro variables. In *SAS Global Forum Annual Conference Proceedings*, 2007. URL <http://www2.sas.com/proceedings/forum2007/113-2007.pdf>. Hands On Workshop, 20 pp.; comparison of methods: making and iterating macro arrays, scanning macro variable, writing calls to macro variable, write to file then include, call execute; using macro function nrstr in call execute argument; 11 examples, bibliography.
- [11] IBM, editor. *HIPO — A Design Aid and Documentation Technique*. IBM Corporation, White Plains, NY, 1974. URL <http://en.wikipedia.org/wiki/HIPO>. Publication Number GC20-1851.
- [12] Donald E. Knuth. *Literate Programming*. CSLI, Stanford, CA, USA, 1992. URL http://en.wikipedia.org/wiki/Literate_programming. 368 pp., 12 chap., index: 10 pp.
- [13] William Lidwell, Kritina Holden, and Jill Butler. *Universal Principles of Design*. Rockport Publishers, Inc, 2010. URL <http://stuffcreators.com/upod/>. 272 pp., 125 chap., index: 5 pp.; each chapter is two pages, each explains core building blocks of design theory.
- [14] Robert C. Martin. *Clean Code*. Pearson Education, Boston, MA, USA, 2009. URL <http://www.pearsonhighered.com/educator/product/Clean-Code-A-Handbook-of-Agile-Software-Craftsmanship/9780132350884.page>. 431 pp., 17 chap., index: 19 pp.; subtitle: handbook of Agile software craftsmanship.
- [15] Steve McConnell. *Code Complete: A Practical Handbook of Software Construction, 2e*. Microsoft Press, Redmond, WA, USA, 2004. URL <http://cc2e.com/>. 960 pp., 35 chap., index: 30 pp.
- [16] Irina Walsh. Pros and cons of interactive SAS(R) mode vs. batch mode. In *Proceedings of the Western Users of SAS Software Annual Conference*, 2010. URL http://www.lexjansen.com/wuss/2010/coders/2937_4_0_COD_Walsh.pdf. Coders' Corner, 9 pp.; autoexec, naming conventions: folders, ODS rtf.